





Issued 06/2020

BPW Transpec Answers to PBS Vehicles and Improved Roll Stability

BPW Transpec has released two new spring trailing arms for AL2 air suspensions with improved roll stiffness ratings. The new spring trailing arms are 65mm thick rather than the original 62mm thick. This improves roll stiffness by at least 25%.



05.082.14.43.2 (AO + AU)



05.082.14.44.2 (AM)

Original Spring	Replacement Spring	Use
1x62	1x65	
05.082.13.95.2	05.082.14.44.2	Already Standard in Australia
05.082.13.96.2	05.082.14.43.2	Available in 3-4 Months

These springs are available in the most common BPW suspension models currently available and can be substituted with no dimensional changes for the trailer builder.

Talk to our sales consultants or engineering team about solutions for your vehicle: -

- Higher rated spring trailing arms
- Adding stabilizer bars
- Wide track axles and single tyre applications

Victoria (Head office)

1-11 Cherry Lane, Laverton North Vic 3026

Phone (03) 9267 2444 **Fax** (03) 9369 4826

New South Wales

10 Squill Place, Arndell Park NSW 2148 **Phone** (02) 8811 7000 **Fax** (02) 8811 7050

Queensland

10 Bernoulli Street, Darra Qld 4076

Phone (07) 3217 0877 **Fax** (07) 3217 0230

Western Australia

1021 Abernethy Road, High Wycombe WA 6057

Phone (08) 9454 4000 **Fax** (08) 9454 4111

1300 651 652 info@bpwtranspec.com.au bpwtranspec.com.au